# PERFECTION EY DESIGN

E JALANEHE





# AVALANCHE



# **Standard Starter Kit**

-Avalanche Cleaning Plant -Installation Kit -Operation Manual -Power Washing Lance -8 Gallon Kerosene Tank -Hookup Kit -Chemical Hose -Water Input Valve -Warm Up Hose -5 Gallon Solution Bottle **Optional Enhancement Features** 

-Pump Out System w/Clutch 14GPM -Carpet Wand -Vacuum Hose Reel -Solution Hose Reel -80 or 110 Gallon Stainless Steel Waste Tanks -Aqua Tank Fresh Water Tank With Chemical Rack -Truck Pan

#### **Performance Enhancing Features**

# **Reduce Wear and Tear**

Heavy duty electric safety clutch allows independent operation of vacuum and pressure system for water damage restoration and pressure washing, which reduces wear and maintenance.

#### **Blower Protection System**

Screens foreign objects from damaging blower system. The front panel access valve allows for easy daily maintenance. Automatic shutoff prevents waste water blowout when waste tank is full, protecting the blower.

# **Complete Dual Wand Capability**

Vacuum suction, solution pressure, and solution heating capabilities combine for dual wand performance.

#### **Safety Protection Shield**

Mounted safety screen prevents access to moving parts. Quick removal allows for easy maintenance access.

# **Be Prepared for Winter**

No Matter what the weather is doing outside you will still deliver the same high cleaning solution temperatures at the same water flow rate to the cleaning surface as you do in the middle of the summer.

# **MACHINE SPECIFICATIONS**

**ENGINE:** Kohler 20 HP Command Pro energy efficient industrial air cooled engine.

VACUUM: Roots 45 URAI blower produces up to 400 cfm.

HEATER: 220 XL On-Demand Fuel Oil Heating System. The 220,000 B.T.U. Fuel Oil Heating System can attain and maintain solution temperatures up to 280 degrees farenheit.

PUMP: Industrial Heavy Duty Cat 3 CP Solution Pressure System. A super powerful, super heavy duty pressure system produces extreme productivity from a truck mounted machine. Adjustable and useable pressures up to 2000 P.S.I. (86 bar) of solution pressure up to 3.7 G.P.M. (13.21 L.P.M.)

# INSTRUMENTATION

Electronic Circuit Breaker Instead of Fuses Tachometer Hour Meter Thermostatically Controlled Water Temperature Water Temperature Monitoring Guage Glycerin Filled Pressure Guage Chemical Flow Metering System

# DIMENSIONS

42.5"W x 48.5"D x 43.5"H Weight 728 lb

# PERFORMANCE

3.7gpm (Max)-2000psi 2.75gpm-1200psi 1.5gpm-500psi-280° (at 1.5gpm) Lab tested with 5.5 tip @ Maximum Settings

# FEATURES

Unprecedented Serviceability Access Easy Access Oil Filter and Oil Drain Inlet Water System Prevents Backflow Vacuum Blower Oiler

Our exclusive "Cool Touch Coil" actually forms the combustion chamber, eliminating troublesome insulation and outside hot spots. It also allows for better air flow which in turn provides better fuel combustion and efficiency. The amazing "Cool Touch Coil" now features our exclusive 7 year warranty!



